

## ! 1. Identification of the substance/preparation

<b>Name of product</b>	<b>GranQuartz 357E Venezian Stone Sealer</b>
<b>Manufacturer/distributor</b>	GranQuartz Stone Care Systems 4963 S.Royal Atlanta Dr., Tucker, GA 30084 Phone 1-800-458-6222
<b>Advice</b>	Techn. Department Phone 1-800-458-6222
<b>Recommended intended purpose(s)</b>	Sealer

---

## 2. Composition/information on ingredients

**Chemical characterization**  
Solvent based sealer

### Hazardous ingredients

CAS-No.	EC-No.	Name	[% weight]	Classification
001330-20-7	215-535-7	xylene	< 20	R10; Xn R20/21; Xi R38
064742-95-6	265-199-0	Solvent naphtha (petroleum), light arom.	> 25	Carc.Cat.2 R45; Xn R65

### Additional advice

Benzene < 0,1 %

---

## 3. Special hazards information for man and environment

### R-phrases

10	Flammable.
20/21	Harmful by inhalation and in contact with skin.
37	Irritating to respiratory system.
51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

---

## 4. First aid measures

### General information

Remove contaminated soaked clothing immediately.

### In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

### In case of skin contact

In case of contact with skin wash off immediately with soap and water.

### In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

### In case of ingestion

Do not induce vomiting.

If swallowed by mistake drink plenty of water and seek medical treatment.

---

## 5. Fire-fighting measures

### Suitable extinguishing material

Foam  
Dry powder  
Carbon dioxide  
sand

---

---

**Extinguishing material that may not be used for safety reasons**

Full water jet

**Special exposure hazards arising from the substance, combustible products or resulting gases**

In case of fire formation of dangerous gases possible.

---

**6. Accidental release measures**

**Personal precautions**

Ensure adequate ventilation.  
Use personal protective clothing.

**Environmental precautions**

Do not discharge into the drains/surface waters/groundwater.

**Methods for cleaning up/taking up**

Take up with absorbent material (e.g. sand, sawdust, general-purpose binder).

---

**7. Handling and storage**

**Advice on safe handling**

Use only in thoroughly ventilated areas.  
Use solvent-resistant equipment.  
Take the usual precautions when handling with chemicals.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking  
Take precautionary measures against static discharges.

**Further information on storage conditions**

Keep container dry, tightly closed and store at cool and aired place.

---

**8. Exposure controls / personal protection**

**Ingredients with occupational exposure limits to be monitored**

CAS-No.	Name	Code	[mg/m <sup>3</sup> ]	[ml/m <sup>3</sup> ]	Remark
	naphtha (petroleum), arom. > 25 %	MAK	200	50	31, TRGS 901-72
001330-20-7	Xylol (alle Isomeren)	MAK	440	100	H

**Respiratory protection**

Breathing apparatus in the event of high concentrations.  
Short term: filter apparatus, filter A

**Hand protection**

chemical-resistant gloves

**Eye protection**

safety goggles

**General protective measures**

Avoid contact with eyes and skin

**Hygiene measures**

At work do not eat, drink and smoke.

---

**9. Physical and chemical properties**

**Form**  
liquid

**Colour**  
colourless, clear

**Odour**  
aromatic

---

Data relevant for safety	Value	Temperature	at	Method	Remark
<b>pH value in delivery state</b>	not applicable				
<b>starts to boil</b>	> 130 °C				
<b>Flash point</b>	> 23 °C				
<b>Lower explosion limit</b>	ca. 0,6 Vol-%				
<b>Upper explosion limit</b>	ca. 8 Vol-%				
<b>Density</b>	ca. 0,9 g/cm <sup>3</sup>				
<b>Solubility in water</b>					more or less insoluble
<b>Viscosity 1 Outflow time</b>	> 30 s			ISO 2431/3 mm	

## 10. Stability and reactivity

**Conditions to avoid**  
 No hazardous reactions known.

## 11. Toxicological information

### Acute toxicity/Irritability/Sensitization

	Value/Validation	Species	Method	Remark
<b>LD 50 acute oral</b>	not determined			
<b>LD 50 acute dermal</b>	not determined			
<b>LC 50 acute inhalation</b>	not determined			

## 12. Ecological information

### Data on elimination (persistence and degradability)

	Elimination rate	Method of analysis	Method	Validation
<b>Physico-chemical degradability</b>	not determined			
<b>Biological degradability</b>	not determined			

## ! 13. Disposal considerations

**! Waste code No.** 07 01 04\* **Name of waste** other organic solvents, washing liquids and mother liquors

**Recommendations for the product**  
 In accordance with regulations for special waste, must be taken to a special waste disposal.

**Recommendations for packaging**

Totally emptied packaging may be taken for recycling.

---

**14. Transport information**

**Land and inland navigation transport (ADR/RID/GGVS/GGVE/ADNR)**

<b>Identification</b>	Flammable liquid, n.o.s. (White spirit) special provision 640
<b>UN-No.</b>	1993
<b>Class</b>	3
<b>PG</b>	III
<b>Hazard No.</b>	30

**Marine transport IMDG/GGV See**

<b>Proper shipping name</b>	Flammable liquid, n.o.s., (White spirit)
<b>UN-No.</b>	1993
<b>Class</b>	3
<b>PG</b>	III
<b>Marine pollutant</b>	No
<b>EmS-No.</b>	3-07

**Air transport ICAO/IATA**

<b>Proper shipping name</b>	Flammable liquid, n.o.s. (White Spirit)
<b>UN/ID-No.</b>	1993
<b>Class</b>	3
<b>PG</b>	III

---

**15. Regulatory information**

**Remarks for classification**

The product is classified and labelled in accordance with EC directives.

**Classification**

<b>Xn</b>	Harmful
<b>N</b>	Dangerous for the environment

**R-phrases**

10	Flammable.
20/21	Harmful by inhalation and in contact with skin.
37	Irritating to respiratory system.
51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**S-phrases**

2	Keep out of the reach of children.
23.3	Do not breathe vapour.
24	Avoid contact with skin.
46	If swallowed, seek medical advice immediately and show this container or label.

**Hazardous ingredients for labeling**

xylene

**National regulations**

<b>Classification according to VbF/ remarks</b>	All
---	-----

<b>Water hazard class</b>	2	VwVwS (17. 05. 1999)
---------------------------	---	----------------------

---

## 16. Other information

### Further information

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

### Wording of the R-phrases specified in chapter 2 (not the classification of the formulation!)

- R 10 Flammable.
- R 20/21 Harmful by inhalation and in contact with skin.
- R 38 Irritating to skin.
- R 45 May cause cancer.
- R 65 Harmful: may cause lung damage if swallowed.